

# ABS

## SUBMITTAL AND DATA SHEET

### JM EAGLE™ ABS SCHEDULE 40/DWV AND/OR WITH CELLULAR CORE PIPE

Specifications: ASTM D2661 and ASTM F628 : :

Listed : ANSI/NSF - DWV, Standard 14, IAPMO

NOM. PIPE SIZE (IN)	O.D. (IN)	NOM. I.D. (IN)	MIN T. (IN)	APPROX. WEIGHT SCH 40/DWV	APPROX. WEIGHT SCH 40/DWV CELLULAR CORE
1-1/2	1.900	1.593	0.145	0.383	0.277
2	2.375	2.049	0.154	0.515	0.363
3	3.500	3.042	0.216	1.069	0.728
4	4.500	3.998	0.237	1.523	1.022
6	6.625	6.031	0.280	—	1.768

: : Available in 5', 10' and 20' lengths.

\* Prior to ordering or specifying, please consult JM Eagle™ for product and/or listings availability.

I.D. : Inside Diameter

O.D. : Outside Diameter

T. : Wall Thickness

#### ABS SCHEDULE 40/DWV

Product Standard: ASTM D2661  
 Pipe Compound: ASTM D3965 Cells Class 4-2-2-2-2  
 Certifications: ANSI/NSF Standard 14  
 End Finish: Plain End  
 Pipe Length: 5, 20 or 20 feet overall  
 Installation: JM Eagle™ Installation Guide

#### ABS SCHEDULE 40/DWV CELLULAR CORE PIPE

Product Standard: ASTM F628  
 Pipe Compound: ASTM D3965 Cells Class 4-2-2-2-2  
 Certifications: ANSI/NSF Standard 14  
 End Finish: Plain End  
 Pipe Length: 5, 10 or 20 feet overall  
 Installation: JM Eagle™ Installation Guide